

Supertex inc.

- OBSOLETE -

VP0300



**P-Channel Enhancement-Mode
Vertical DMOS FETs**

Ordering Information

BV _{DSS} / BV _{DGS}	R _{DS(ON)} (max)	I _{D(ON)} (min)	Order Number / Package
			TO-92
-30V	2.5Ω	-1.5A	VP0300L

Features

- ☐ Free from secondary breakdown
- ☐ Low power drive requirement
- ☐ Ease of paralleling
- ☐ Low C_{iss} and fast switching speeds
- ☐ Excellent thermal stability
- ☐ Integral Source-Drain diode
- ☐ High input impedance and high gain
- ☐ Complementary N- and P-channel devices

Applications

- ☐ Motor controls
- ☐ Converters
- ☐ Amplifiers
- ☐ Switches
- ☐ Power supply circuits
- ☐ Drivers (relays, hammers, solenoids, lamps, memories, displays, bipolar transistors, etc.)

Absolute Maximum Ratings

Drain-to-Source Voltage	BV _{DSS}
Drain-to-Gate Voltage	BV _{DGS}
Gate-to-Source Voltage	± 20V
Operating and Storage Temperature	-55°C to +150°C
Soldering Temperature*	300°C


* Distance of 1.6 mm from case for 10 seconds.

Advanced DMOS Technology

These enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Package Options



Note: See Package Outline section for dimensions.

Thermal Characteristics

Package	I_D (continuous)*	I_D (pulsed)	Power Dissipation $T_C = 25^\circ\text{C}$	θ_{ja} $^\circ\text{C/W}$	θ_{jc} $^\circ\text{C/W}$
TO-92	-0.32A	-0.87A	1.0W	170	125

* I_D (continuous) is limited by max rated T_J .

- OBSOLETE -

Electrical Characteristics (@ 25°C unless otherwise specified)

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	-30			V	$V_{GS} = 0V, I_D = -10\mu A$
$V_{GS(th)}$	Gate Threshold Voltage	-1.0	-1.8	-4.5	V	$V_{GS} = V_{DS}, I_D = -1mA$
I_{GSS}	Gate Body Leakage			-100	nA	$V_{GS} = \pm 30V, V_{DS} = 0V$
I_{DSS}	Zero Gate Voltage Drain Current			-10	μA	$V_{GS} = 0V, V_{DS} = -25V$
				-500		$V_{GS} = 0V, V_{DS} = -25V$ $T_A = 125^\circ\text{C}$
$I_{D(ON)}$	ON-State Drain Current	-1.5	-1.7		A	$V_{GS} = -12V, V_{DS} = -10V$
$R_{DS(ON)}$	Static Drain-to-Source ON-State Resistance			2.5	Ω	$V_{GS} = -12V, I_D = -1A$
G_{FS}	Forward Transconductance	200			mS	$V_{DS} = -10V, I_D = -0.5A$
C_{ISS}	Input Capacitance			150	pF	$V_{GS} = 0V, V_{DS} = -15V$ $f = 1MHz$
C_{OSS}	Common Source Output Capacitance			120		
C_{RSS}	Reverse Transfer Capacitance			60		
$t_{(ON)}$	Turn-ON Time			30	ns	$V_{DD} = -25V, I_D = -1A$ $R_{GEN} = 25\Omega$
$t_{(OFF)}$	Turn-OFF Time			30		
V_{SD}	Diode Forward Voltage Drop		-1.2		V	$V_{GS} = 0V, I_{SD} = -1.5A$

Notes

- All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300 μs pulse, 2% duty cycle.)
- All A.C. parameters sample tested.

Switching Waveforms and Test Circuit

